


## UHD35

4K UHD gaming and home entertainment projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 3600 lumens
- Supports 1080p 240Hz for smooth gaming and an ultra-low input lag of 4.2ms
- Full 3D compatible

Immerse yourself in a world of Ultra HD gaming, live sports, TV shows and movies. The UHD35 delivers impressive 4K cinema-quality images, lightning-fast input lag as low as 4.2ms and a high refresh rate of 240Hz for silky smooth gaming.

TV and movie fans can also enjoy excellent colour depth, crystal clear detail, and sparkling contrast for a stunningly immersive experience.

Packed with the latest technology and features, this stylish projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D and two HDMI 2.0 ports. Perfect for enjoying life-like big-screen entertainment in any living space.



## **Specifications**

Specifications	
Display/image	
Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	3.600 lumens
Contrast ratio	1.000.000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction -	+/-40°
horizontal	
Keystone correction -	+/-40°
vertical	
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	80%
Screen size	0.84m ~ 7.62m (33" ~ 300") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
	4000 (Bright), 13000 (Byharlic), 10000 (Eco)
Optical	1.5.4 . 1.00.4
Throw ratio	1.5:1 ~ 1.66:1
Projection distance (m)	1.21m - 9.9m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.84 mm~17.42mm/0.624"~0.686"
Lens shift	Vertical +0%
Native offset	105%
Connectivity	
Connections	Increase On LIDNALO ON The VOA (VDIn Day/DOD) of the Assets
Connections	Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power
	1.5A
	Control 1 x RS232, 1 x 12V trigger
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD,
	XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),
	1080p(50/60Hz), 2160p(50/60Hz)
3D compatibility	Frame-pack: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
-	
OSD / display languages	10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
O	
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Pomoto control	,
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	10W
In the box	AC power cord
	Remote control
	2x AAA batteries
Innet Inn	Basic user manual
Input lag	4.20ms
Power	100 0101 50 0011
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption	0.5W
(standby)	
Power consumption (min)	220W
Power consumption (max)	305W
Weight and dimensions	
Dimensions (W x D x H)	315 x 270 x 118
mm	

5.1 kg

3.9 kg

Gross weight

Net weight



