TX-NR838 7.2-Channel Network A/V Receiver



Spellbinding Entertainment, However You Like It

Destined to intoxicate hi-fi enthusiasts as much as film lovers, the TX-NR838 boasts the absolute latest in high-resolution A/V processing. This heavyweight marries Onkyo's Emotion, Delivered high-current amplification with Dolby Atmos® multidimensional sound*, a format that locates and moves directional audio above and around the listener in a seamless sphere of living sound. Thanks to the massive customized transformer and discrete Three-Stage Inverted Darlington Circuitry, you can feel the awesome power of multiplex movies in your own home. Hi-fi credentials are further cemented with Pure Direct Analog Path, a selectable mode that shuts down all digital circuitry when you're listening to LPs or other analog audio sources for pristine sound. Devotees of high-resolution can stream their network-attached hi-res albums using the remote app and Wi-Fi®, or get an instant fix with a smartphone and DSP-enhanced Bluetooth. The TX-NR838 is also packed with cutting-edge features for movies and gaming, with 4K/60 Hz-ready HDMI® terminals, HDCP 2.2 for future Ultra HD video streaming, and the sheer power you need for a convincing surround-sound experience. *Firmware update required.

ADVANCED FEATURES

- Supports New Dolby Atmos[®] Format for Exciting
- Multidimensional Sound THX[®] Select2[™] Plus Certified for Cinema Reference Sound
- 4K/60 Hz-Capable HDMI® Terminals for Ultra HD Entertainment*
- Supports HDCP 2.2^{*2} Copy Protection for Future 4K Streaming, Broadcasting, and Premium Studio Content
- · Zone 2 HDMI Output for HD Video in a Second Room
- Built-in Wi-Fi[®] Certified Wireless LAN Capability
- Bluetooth Version 2.1 + EDR Capability (Compatible Profile:A2DP v1.2,AVRCP v1.3) with Advanced Music Optimizer DSP Technology
- Three-Stage Inverted Darlington Circuitry on All Channels · Customized Capacitors and Transformer for High-Current Capability
- Pure Direct Analog Path Mode for Interference-Free Hi-fi Stereo Listening
- HDMI[®] Video Upscaling to 4K with Qdeo[™] Processing Technology by Marvell
- Internet Radio and Music Streaming Subscription Services
- Included (TuneIn Radio, Pandora®, Spotify, AUPEO!, and Deezer)*3
- Play Compressed, Lossless, and Hi-res Audio via Local Network (MP3, WMA, WMA Lossless, FLAC, WAV, Ogg Vorbis, AAC, Apple Lossless, DSD 5.6 MHz, LPCM¹⁴, and Dolby[®] TrueHD)
- · AccuEQ Room Calibration with Mic for Clear and Balanced Sound
- Dolby[®] Pro Logic[®] IIz Upmixing for 7.1-Channel Surround Sound
- Advanced Music Optimizer to Improve Compressed Digital
- Audio Quality (Bluetooth Included)
- Control and Stream with Free Onkyo Remote Streaming Apps
- for iPod touch/iPhone^{®5} and Android Devices^{®6} Frontside MHL[™] for 1080p Video and Stills from Smartphone and Tablet
- Overlaid Input Source Preview with InstaPrevue[™] Technology
- Bi-Amping Capability for Front Channels

- Powered Zone 2 and Zone 2/3 Pre/Line-Outs for Distributed Audio Playback
- Whole House Mode for Synchronized Housewide Audio
- 7.2 Multichannel Pre-Outs
- PM Bass for Deep Bass and Clear Mid-Range
- PTP Dass for Deep Dass and User PIIO-Kange 14/K00 Hz wideo is supported on HDMI Inputs 1/20/4, the fornsize input, Main Out, and Sub Out? 2 HDCP 2.2 is supported on HDMI Input 3 and Main Out only: *3 Availability of services depends on region. Some services may require a paid subscription and firmware update. Availability of third-party services advertised here is occurate at the time of publication, but may be subject to change without notice. *4 LPCM is supported via DLNA only. *5 Compatible with Pdd touch (2rd generation or Inled) and IPM on SSG or later.All models require IOS 4.2 or later. *6 Requires Android OS 2.1 or later.

AMPLIFIER FEATURES

- 180 W/Ch (6 Ω, 1 kHz, 1% THD, 1 Channel Driven, IEC); 215 W/Ch (6 Ω, 1 kHz, 1 Channel Driven, IEITA)
- WRAT (Wide Range Amplifier Technology), H.C.P.S. (High Current Power Supply) Massive High Power Transformer, Discrete Output Stage Circuitry, and Optimum Gain Volume Circuitry
- PLL (Phase Locked Loop) Jitter-Cleaning Circuit Technology for S/PDIF Audio

PROCESSING FEATURES

- HDMI for 4K/60 Hz Video, 3D, Audio Return Channel, DeepColor[™], x.v.Color[™], LipSync, Dolby Atmos[®], Dolby[®] TrueHD, DTS-HD Master Audio[™], DVD-Audio, Super Audio CD, Multichannel PCM, and CEC
- TI Burr-Brown 192 kHz/24-Bit DAC (8 Channels x 1) • Dual 32-Bit Digital Signal Processing Engines
- 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Theater-Dimensional Virtual Surround Function
- Direct Mode and Pure Audio Mode

CONNECTION FEATURES

• 7 HDMI Inputs (I Front/6 Rear), Zone I and Zone 2 Outputs Mass Storage Class USB Memory Playback Capability

ONKYO

- · Component Video Switching (I Input and I Output)
- 4 Composite Video Inputs (I Front/3 Rear) and I Output • 5 Digital Audio Inputs (2 Optical and 3 Coaxial)
- 7 Analog Audio Inputs (I Front/6 Rear)
- Phono Input (MM) for Turntable Connection
- IR Input, I2V Trigger Out (Zone 2), and RS232 Port • 2 Parallel Subwoofer Pre-Outs

OTHER FEATURES

- Independent Crossover Adjustment for Each Channel (40/50/ 60/70/80/90/100/120/150/200 Hz)
- A/V Sync Control (Up to 800 ms in 10 ms Steps at 48 kHz) • Graphical Overlaid On-Screen Display (OSD) via HDMI with Quick Set-Up
- Hybrid Standby Function with HDMI Passthrough
- Smart Grid-Ready
- Tone Control (Bass/Treble) for Front L/R Channels 3-Mode Display Dimmer (Normal/Dim/Dimmer, Volume Knob LED On/Off[®])
- RDS (PS/RT/PTY/TP) (European Model Only)
- 40 FM/AM Random Presets
- Certified with DLNA Version 1.5
- Firmware Updates via Ethernet and USB
- RIHD (Remote Interactive Over HDMI) for System Control Aluminum Front Panel and Volume Control Knob
- Preprogrammed RI (Remote Interactive) Remote Control knob LED i ivs off when displa

TX-NR838 7.2-Channel Network A/V Receiver

Dolby Atmos® Multidimensional Sound

Onkyo is among the first to introduce Dolby Atmos sound to home cinemas. Dolby Atmos uses object-oriented mixing techniques to layer independent audio elements through discrete channels, placing and moving sound effects above and around the listener with astonishing realism. The format adapts to any home cinema layout augmented by two or more in-ceiling height speakers or Dolby Atmos-enabled front speakers to bring sound alive from all directions.

Onkyo Sound is Emotion, Delivered

Drivers don't judge sports cars on top speed alone. Acceleration, comering, and braking are equally important. It's the same with AV receivers—wattage is an indication of loudness, not sound quality. The real test is current. High instantaneous current enhances speaker control for accurate and musical audio reproduction, from delicate piano passages to the full-throated roar of an orchestra. It's the cornerstone of our amplification philosophy, and no one can match Onkyo for dynamic driving power. We don't just translate signals into sound. We create sound you can feel.

Engineered for Pure Exhilaration

High current is achieved with Wide Range Amplifier Technology (WRAT). The design is built around a custom high-output transformer, customized 15,000 µF capacitors, and low-impedance copper bus-plates. Three-Stage Inverted Darlington Circuitry amplification features a discrete low-impedance output stage with high-current transistors for instantaneous power and extremely low distortion. The culmination of over 60 years' audio engineering know-how, WRAT preserves the life and character of the master recording.

THX[®] Select2[™] Plus for Reference-Level Sound

THX certification guarantees the same high volume, lowdistortion sound you experience in a multiplex cinema. YourTX-NR838 receiver passed more than 2,000 laboratory tests to ensure every aspect of audio performance meets THX standards for cinema-reference sound. THX Select2 Plus is recommended for screen-to-seat viewing distances of three to four meters.

Pure Direct Analog Path for Interference-Free Hi-fi Amplification

Pure Direct Analog Path mode brings higher fidelity to vinyl, SACD, or CD playback via your home cinema. With this mode engaged, every digital circuit is physically shut down to prevent interference. Signals pass directly from the phono or analog audio inputs to the amplifiers and arrive at your front loudspeakers in pure analog form. The improvement in audio quality is quite dramatic, with the rich tonal character of your LPs shining through. This mode lets your AV receiver double a dedicated all-analog hi-fi stereo amplifier.

Latest HDMI® for 4K/60 Hz Video and HDCP 2.2

All HDMI terminals (except Input 5/6) feature the latest HDMI supporting 4K video at 60 frames per second and 21.9 cinema aspect. Now you can add enveloping surroundsound to next-generation Ultra HD games and video for truly breathtaking entertainment. The TX-NR838 also supports HDCP 2.2 copy protection, which is essential for viewing future premium streamed and broadcast Ultra HD and Full HD content.

4K Video Upscaling with Qdeo[™] Technology

The TX-NR838 features Qdeo[™] video processing technology to upscale low-resolution video to liquid-smooth 1080p (for HDTV) and 4K for compatible displays. This means video from older games and DVDs looks sharp and clean, giving your old favorites a new lease on life.

Share Your HD Video Sources in Two Zones

Use the HDMI Sub Out to connect a second display in another room. This allows you to route 1080p content from the media players connected to your receiver and play it back on another TV with easy smartphone control.

Wi-Fi® and Bluetooth Inside

Wi-Fi and Bluetooth technology are built in. Download our free app and you've got a graphic remote control with a range of streaming options in the palm of your hand, or pair your Bluetooth-capable device and send almost any audio to your home cinema. With Advanced Music Optimizer enhancement, music via Bluetooth never sounded so good.

Stream Music from Smartphone and Tablet

For lossless audio streaming tap on the Onkyo Remote App icon on your smartphone to find your music loaded and ready with familiar song organization and playback controls. You can also browse and stream millions of tracks on Spotify and Deezer (as well as a variety of internet radio services) from within the app.

Stream Network-Attached Hi-res Music via Remote App

You can also use the app to locate and stream your 192/24 and 96/24 hi-res albums (including 5.6 MHz DSD) via DLNA. Bask in the extraordinary clarity, depth, and detail of highresolution music.

Powered Multi-Zone Audio and Bi-Amping

Powered Zone 2 speaker terminals let you power audio in another room equipped with speakers, controlling content in both zones via smartphone. You can also assign surround back channels to bi-amp your front loudspeakers.

AccuEQ Room Calibration

AccuEQ optimizes surround-sound and two-channel audio to suit your listening space. In particular, AccuEQ extracts the best possible performance from your front speakers to make stereo listening more dynamic and exciting. The system analyzes speaker setup and room acoustics from one listening position (which simplifies the calibration process) and optimizes frequency response and output levels for maximum clarity.

SPECIFICATION	S
Amplifier Section	
Power Output	
All Channels	180 W/Ch (6 Ω, 1 kHz, 1% THD,
	I Channel Driven, IEC)
	215 W/Ch
	(6 Ω, 1 kHz, 1 Channel Driven, JEITA)
Dynamic Power	300 W (3 Ω, Front)
	250 W (4 Ω, Front)
	150 W (8 Ω, Front)
THD+N (Total Harmonic	Distortion + Noise)
	0.08% (20 Hz–20 kHz, Half Power)
Damping Factor	60 (Front, I kHz, 8 Ω)
Input Sensitivity and Impe	dance
. , .	200 mV/47 kΩ (Line)
	2.5 mV/47 kΩ (Phono MM)
Rated RCA Output Level and Impedance	
	200 mV/470 Ω (Line Out)
Maximum RCA Output L	evel and Impedance
	4.6 V/470 Ω (Line Out)
Phono Overload	70 mV (MM, 1 kHz, 0.5%)
Frequency Response	5 Hz–100 kHz/+1 dB, -3 dB (Direct Mode)
Tone Control	±10 dB, 20 Hz (Bass)
Ione Control	±10 dB, 20 kHz (Treble)
Signal to Nicisa Patio	106 dB (Line, IHF-A)
Signal-to-Noise Ratio	80 dB (Phono MM, IHF-A)
Saalaa Imaadaaca	·····
Speaker Impedance	$4 \Omega - 16 \Omega$ or $6 \Omega - 16 \Omega$
Video Section	
Input Sensitivity/Output Level and Impedance	
Video	1.0 Vp–p/75 Ω (Component Y)
	0.7 Vp-p/75 Ω (Component PB/CB, PR/CR)
••••••	I.0 Vp–p/75 Ω (Composite)
Component Video Frequency Response	
	5 Hz–100 MHz/+0 dB, -3 dB
Tuner Section	
Tuning Frequency Range	
FM , , U	87.5 MHz-108 MHz
AM	522 kHz–1,611 kHz
	530 kHz–1,710 kHz
FM/AM Preset Memory	40 Stations
General	
Power Supply	AC 220-240 V~, 50/60 Hz
	· · · · · · · · · · · · · · · · · · ·
Power Consumption	720 W
No-Sound Power Consur	nption 90 W
Standby Power Consump	
	0.15 W
Dimensions (W x H x D)	
	(Height 261.2 mm with antennas raised)
Weight	15.5 kg
CARTON	
CARTON	

CARTON

 Dimensions (W x H x D)
 576 × 331 × 508 mm

 Weight
 18.5 kg

Supplied Accessories

 Indoor FM antenna •Antenna isolator" •AM loop antenna • Color labels for speaker cables • Speaker setup microphone • Instruction manual • Remote controller • AA (R6) batteries" × 2 *Included with Chinese model only.

**Not included with Chinese model



Due to a policy of continuous product improvement, Onlyio reserves the right to charge specifications and appearance without notice. THX, the THX logs, and Select2 are trademarks of THX Ltd. THX and the THX logs are registered in the US and other jurisdictions, All rights reserved. Manufactured under icense from Doby Laboratories. Doby, Atmos, ProLogic, and the double-D symbol are trademarks of Doby Laboratories. FOr DTS patents, see http://patents.dts.com.Manufactured under icense from DTS Licensing Linuted. DTS. DTS-ML by the Symbol. A B TS and the Symbol together are registered trademarks, and DTS-HD Master Audio is a trademark of DDS, Inc. @ DTS, Inc. @



Onkyo Corporation Kitahama Chuo Bidg. 2-2-22 Kitahama, Chuo-ku, Osaka 541-001 JAPAN http://www.onkyo.com/ Onkyo Europe Electronics GmbH Lugnitzertarsas 6, 82104 Grobenzell, GERMANY Tei: 49-8142-4208-10 Fax: 49-8142-4208-20 http://www.eu.onkyo.com/ Onkyo Europe Electronics GmbH (UK Branch) Meridien House, Ground floor, 69-71 Clarendon Road, Watford, Heritordshire, WD17 DS UNITED KINGDOM Tei: +44-871-200-1996 http://www.onkyo.co.uk/ Onkyo China Limited Unit 1033, 10/F. Stor House, No. 3, Salisbury Road, Tamis Pha Taik, Kowloon, Hong Kong, CHINA Tei: 852-2428-9039 http://www.hk.onkyo.com(Hong Kong) http://www.cn.onkyo.com(Mainland)