

# PROFILE 918

## Product specification sheet



### Features

- **2<sup>1/2</sup>-way** bass-reflex floor standing loudspeaker
- Sophisticated **design** for maximum performance and aesthetic integration capability.
- Bended, **multi-fold MDF** cabinet for toughness and optimal damping.
- New **aluminum/magnesium alloy inverted dome** tweeter, Poron® surround, frequency response up to 30kHz, SACD and DVD-Audio compatibility.
- **New generation** woofer composite **W sandwich cones**.
- **OPC** filtering for perfect phase alignment and optimal directionality.
- **Three finishes**, natural wood veneering: Classic, Signature, Style.

### Technical specifications

Type	2 <sup>1/2</sup> -way bass-reflex floor standing loudspeaker
Drivers	1" (2.5cm) Al/Mg inverted dome tweeter 6 <sup>1/2</sup> " (16.5cm) W cone woofer, 32mm voice-coil 6 <sup>1/2</sup> " (16.5cm) W cone midbass, 40mm voice-coil
Frequency response (+/-3dB)	40Hz to 30.5kHz
Sensitivity (2,83V/1m)	90dB
Nom. impedance	8Ω
Min. impedance	3.2Ω at 110Hz
Max. power handling	175W
Crossover frequency	180Hz / 2600Hz
Dimensions (HxWxD)	39"x9"x13.8" (990x230x350mm)
Net weight	43lbs (19.5kg)

