

# PROFILE CC 908

## Product specification sheet

3" W cone mid-range

Aluminum/magnesium alloy  
inverted dome tweeter

Bended, multi-fold MDF cabinet



Aerodynamic port

6<sup>1</sup>/<sub>2</sub> (165mm) W  
cone woofer

Stylish driver, architecturally formed,  
acoustically transparent speaker grill



### Features

- **3-way** bass-reflex with coherent phase and constant energy.
- Optimized fitting with Profile 908/918 and 928 in multi-channel mode.
- A sophisticated design for maximum **performances and esthetic integration** capability.
- **Bended multi-fold MDF** cabinet for toughness and optimal damping.
- **New Al/Mg alloy inverted dome tweeter**, Poron® surround, frequency response up to 30kHz, SACD and DVD-Audio compatibility.
- **New generation** woofer composite "W" sandwich cones.
- New 3" mid-range, ultra-compact with **very low directivity**.
- **OPC** filtering for perfect phase alignment and optimal directivity.
- **Three finishes**, natural wood veneering.
- 15<sup>3</sup>/<sub>4</sub>" (40cm) dedicated optional stand **SCC 908**.

### Technical specifications

Type	3-way center loudspeaker
Drivers	1" (25mm) Al/Mg inverted dome tweeter, 3" (8cm) "W" cone midrange, 1" voice-coil 2x6 <sup>1</sup> / <sub>2</sub> " (165mm) "W" cone woofer, 1" voice-coil
Frequency response (+/-3dB)	65Hz to 30.5kHz
Sensitivity (2,83V/1m)	91dB
Nom. impedance.	8Ω
Min. impedance	4.2Ω at 150Hz
Maximum power handling	150W
Crossover frequency	500Hz / 2 600Hz
Dimensions (HxWxD)	8 <sup>1</sup> / <sub>16</sub> "x24 <sup>7</sup> / <sub>8</sub> "x12 <sup>3</sup> / <sub>4</sub> " (205x632x324mm)
Net weight	32lbs (14.5kg)



**FOCAL**  
the spirit of sound