

# PROFILE SR 908

## Product specification sheet

Stylish, driver protective grills

Wall bracket mounting

Aluminum/magnesium alloy inverted dome tweeters

Wall Boost Control System

MDF cabinet

6<sup>1</sup>/<sub>2</sub>" (165mm) "W" cone woofers

### Features

- 2-way **bipolar effects** loudspeaker, 4 speakers
- High **performance, compact** size
- **Wide dispersion design**
- New **aluminum/magnesium alloy inverted dome tweeter**, Poron® surround, frequency response up to 30kHz
- Latest generation **composite "W" sandwich** cones
- **OPC crossover** for perfect phase alignment
- Easy to install **wall bracket system**
- **Wall Boost Control** : to reduce the " wall effect "
- Two finishes, **Style** (silver) and **Classic/Signature** (dark grey)

### Technical specifications

Type	2-way, sealed, bipolar effects loudspeaker
Drivers	Two 1" (2.5cm) Al/Mg inverted dome tweeters Two 6 <sup>1</sup> / <sub>2</sub> " (16.5cm) "W" cone woofers, 1 <sup>1</sup> / <sub>4</sub> " voice-coil
Frequency response (+/- 3dB)	75Hz to 30.5kHz
Sensitivity (2.83V/1m)	91dB
Nominal impedance	8Ω
Minimum impedance	5.2Ω at 350Hz
Max Power handling	175W
Crossover frequency	2600Hz
Dimensions (HxWxD)	11 <sup>5</sup> / <sub>8</sub> "x15 <sup>7</sup> / <sub>8</sub> "x7 <sup>5</sup> / <sub>8</sub> " (295x403x194mm)
Weight	19.4lbs (8.8kg)

